

M Y S T I K [®] C H A I N S A W O I L

Date 02/06

DESCRIPTION:

Mystik Chain Saw Oil is a high performance oil engineered for two-cycle chain saw engines. It is formulated to prevent excessive wear and cut deposits to a minimum. It prevents plug fouling, port plugging, ring sticking, and maintains engine cleanliness. Recommended for Homelite, Husqvarna, Poulan, Pioneer, Stihl, McCulloch and other leading chain saw brands. It is the choice of many logging industry professionals. Mix in accordance with manufacturer's recommendation for gasoline/oil ratio.

FEATURES:

Specially formulated and tested for use in two-cycle engines. Mix in accordance with manufacturer's recommendation for gasoline/oil ratio. Mystik Chain Saw Oil assures easy starts, reduces deposits, and extends spark plug life.

NOTE: Protect your chain saw's bar and chain with Mystik Bar and Chain Lubricant, Code 663605002.

TYPICAL PROPERTIES:

MYSTIK CHAIN SAW OIL

Material Code	663070002
SAE Grade	30
Gravity, ASTM D 4052 at 60°F, °API	29.4
Density, lb/gal at 60°F	7.3
Flash Point, COC, °F (°C)	440 (227)
Pour Point, °F (°C)	5 (-15)
Viscosities:	
cSt at 40°C	100.8
cSt at 100°C	11.2
cSt, (SUS) at 100°F	113 (525)
cSt, (SUS) at 210°F	11.5 (64.7)
Viscosity Index	97
Flash Point, COC, °F (°C)	440 (227)
Pour Point, °F (°C)	5 (-15)
Appearance, Color	Blue-Green