

MYSTIK® LUBRICANTS
TWIN DISC FLUID



Date 01/10

For 3-Stage Torque Converters made by the Twin Disc Clutch Company Approved List S364C

DESCRIPTION:

Mystik Lubricants Twin Disc Fluid is a very low viscosity, low friction fluid with antifoam inhibitor and is for specialized applications. Certain Twin Disc Clutch company converters do not use this type fluid. May also be used as an ISO 2 Spindle Oil.

TYPICAL PROPERTIES:

MYSTIK® LUBRICANTS TWIN DISC FLUID

Material Code	663540002
Viscosity Grade:	
SAE Grade	Thinner than SAE 5W
ISO Grade (Approx.)	2
Gravity, ASTM D 4052, °API	43.0
Density, lb/gal	6.75
Specific Gravity	0.811
Viscosities:	
at 40°C, cSt	2.5
at 100°F, cSt (SUS)	2.67 (34.3)
Flash Point, ASTM D 92, °F (°C)	187 (86)
Fire Point, ASTM D 92, °F (°C)	198 (92)
Pour Point, ASTM D 97, °F (°C)	-40 (-40)
Distillation, IBP	378
Aniline Point, ASTM D 611, °F (°C)	180 (82)
Carbon Residue, Weight %	0.01
Color	Red

NOTE: Certain Twin Disc Company converters do not use this type fluid. Make certain the unit involved requires a fluid listed on Twin Disc Approved List Sheet "S364C."