

Mystik® Twin Disc Fluid

OVERVIEW



- A very low-viscosity, low-friction fluid designed for specialized applications.

FEATURES & BENEFITS



- Contains foam inhibitor.
- Approved by Twin Disc Clutch Company for certain applications.

APPLICATIONS



- For 3-stage torque converters made by the Twin Disc Clutch Company (approved list S364C).
- May be used as an ISO 2 spindle oil.
- Certain Twin Disc Clutch Company converters do not use this type of fluid; consult owner's manual for proper lubricant selection.

PROPERTIES**Typical Properties for Mystik Twin Disc Fluid:**

Material Code	663540002
Viscosity Grade:	
SAE Grade	Thinner than SAE 5W
ISO Grade (Approx.)	2
Gravity, ASTM D4052, °API	43.0
Density, lb/gal	6.75
Specific Gravity	0.811
Viscosities:	
at 40°C, cSt	2.5
at 100°F, cSt (SUS)	2.67 (34.3)
Flash Point, ASTM D92, °F (°C)	187 (86)
Fire Point, ASTM D92, °F (°C)	198 (92)
Pour Point, ASTM D97, °F (°C)	-40 (-40)
Distillation, IBP	378
Aniline Point, ASTM D611, °F (°C)	180 (82)
Carbon Residue, Weight %	0.01
Color	Red

NOTE: Certain Twin Disc Company converters do not use this type fluid. Make certain the unit involved requires a fluid listed on Twin Disc Approved List Sheet "S364C."

Mystik is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.