M Y S T I K® M U L T I - P U R P O S E A T F

Date 01/10

DESCRIPTION:

Mystik Multi-Purpose ATF is a multi-function, automatic transmission fluid manufactured from selected high-quality base stocks and premium additives. It protects transmission parts against rust, corrosion, and wear. It is dyed red for leak detection and is engineered to give superior protection and performance. Mystik Multi-Purpose ATF is recommended where the following lubricants are specified: General Motors transmissions calling for DEXRON®-III, DEXRON®-IIE and DEXRON®-II fluids; Ford transmissions calling for MERCON® type ATF's; Allison Transmission Division (C-4).

FEATURES:

- A single fluid for a wide variety of power transmission uses: automotive automatic transmissions, industrial torque converters, sensitive hydraulic fluid applications, power-shift transmissions, and Allison automatic transmissions.
- Excellent stability for long life service
- Anti-wear, anti-leak, anti-foam treated
- Detergent inhibitor provides gum-up resistance
- Can be used industrially as an excellent multi-viscosity, "all weather" hydraulic fluid, torque converter fluid and as a cold temperature gear lubricant
- Meets the performance requirements of the following hydraulic fluid, power-shift transmission fluid and automatic transmission fluid specifications:

Denison HF-0, HF-1, and HF-2 requirements	DEXRON-III
Sperry Vickers M-2950-S and I-286-S	Ford M2C138CJ
Caterpillar TO-2 (SAE 10W)	Ford M2C166H
Renk Doromat 873 and 874	Ford MERCON (Approved)
Allison Type C-3 and C-4	Daimler-Benz DKA

APPLICATIONS:

Recommended for use in automatic transmissions manufactured by General Motors and Ford for model years 2006 and prior (except those calling for FORD Type "F" Fluid, MERCON® SP, MERCON® V, DEXRON® VI and CVT fluids). Suitable for use in foreign cars and trucks requiring the use of DEXRON-III, DEXRON-IIE, DEXRON-II fluids, and MERCON type ATF's.

TYPICAL PROPERTIES:

MYSTIK® MULTI-PURPOSE ATF

Material Code	**633135002**
Gravity, ASTM D 4052, °API	33.0
Pounds Per Gallon	7.16
Flash Point, ASTM D 92, COC, °F (°C)	424 (218)
Pour Pont, ASTM D 97, °F (°C)	-54 (-48)
Viscosity, ASTM D 445, cSt at 40°C	34.3
cSt at 100°C	6.95
ASTM D 2983, cP at -20°C	1,020
cP at -40°C	15,100
Vicosity Index, ASTM D 2270	169
Color	Red