

Mystik® Multi-Purpose ATF

OVERVIEW




- Multi-function, automatic transmission fluid manufactured from high-quality base stocks and premium additives to protect transmission parts against rust, corrosion, and wear.
- Engineered to give superior protection and performance where the following lubricants are specified: General Motors transmissions calling for DEXRON®-III, DEXRON®-IIE and DEXRON®-II fluids; Ford transmissions calling for MERCON® type ATFs; Allison Transmission Division (C-4).

FEATURES & BENEFITS



- A single fluid for a wide variety of uses: automotive automatic transmissions, industrial torque converters, sensitive hydraulic fluid applications, powershift transmissions, Allison automatic transmissions, and power steering fluids.
- Excellent stability for long service life.
- Treated to prevent wear, leaking, and foaming.
- Detergent inhibitor provides gum-up resistance.
- Dyed red for leak detection.

APPLICATIONS



- For use in automatic transmissions manufactured by General Motors and Ford for model years 2006 and prior (except those calling for FORD Type F Fluid, MERCON® SP, MERCON® V, MERCON® LV, DEXRON® -VI, and CVT fluids).
- Suitable for use in foreign cars and trucks requiring the use of DEXRON® -III, DEXRON® -IIE, DEXRON® -II fluids, and MERCON® type ATFs.
- Meets the performance requirements of the following hydraulic fluid, powershift transmission fluid, and automatic transmission fluid specifications:

Vickers M-2950-S and I-286-S	GM DEXRON® -IIIG/H, IID/E
Caterpillar TO-2	Ford MERCON®
Allison Type C-4	Ford ESP-M2C166H
Allison TES 389B	Chrysler ATF +3 (MS 7176E)
- Suitable for use where the following specifications are recommended:
 - Audi G 052 162-A1/A2 (ZF Lifeguardfluid 5)
 - MAN 339A
 - Volvo 97325, 97335, CE 97340
 - VW G-052 025 A2; G-052 162
 - ZF all 3 & 4 speed transmission; ZF TE-ML 05L, TE-ML 09 and TE-ML 21L
- May be used industrially as an excellent multi-viscosity, all-weather hydraulic fluid, torque converter fluid, and low-temperature gear lubricant.
- Refer to equipment owner's manual for proper lubricant recommendation.

PROPERTIES**Typical Properties for Mystik Multi-Purpose ATF:**

Material Code	633135002
Gravity, ASTM D4052, °API	33.0
Pounds Per Gallon	7.16
Flash Point, ASTM D92, COC, °F (°C)	424 (218)
Pour Point, ASTM D97, °F (°C)	-54 (-48)
Viscosity, ASTM D445	
cSt at 40°C	34.3
cSt at 100°C	6.95
ASTM D2983	
cP at -20°C	1,020
cP at -40°C	15,100
Vicosity Index, ASTM D2270	169
Color	Red

©2019 CITGO Petroleum Corporation

The Mystik Lubricants name, logo and all related marks are registered trademarks protected by federal law. All other registered trademarks or trademarks are the property of their respective owners.