

**MYSTIK® ANTI-LEAK
INDUSTRIAL OIL**



Date 01/10

A Versatile and Widely Varied Purpose Lubricant

DESCRIPTION:

Mystik Anti-Leak Industrial Oil is a very wide temperature range, multiple viscosity grade oil specially treated for maximum leakage resistance. Fortified with antiwear, antifoam, antirust, and antioxidant stabilizer additives for long life. It has a special “antisplatter” additive for splash resistance and a slower “drip off” rate. While primarily used as a combination replacement for individual ISO, 46, 68, and 100 grade hydraulic fluids, this product is also being used as a medium viscosity way oil, a winter rock drill oil, a compressor lubricant, a “non-drip” general purpose shop oil, and as a circulating oil for gears and bearings.

FEATURES:

- A very wide temperature range, multiple viscosity grade oil, specially treated for leakage resistance. Fortified with antiwear, antifoam, antirust, and antioxidant stabilizer additives for long life.
- Has a special “antisplatter” additive for splash resistance and a slower “drip off” rate.
- While primarily used as a combination replacement for individual grade hydraulic fluids, this product is also being used as a medium viscosity way oil, a winter rock drill oil, a compressor and vacuum pump lubricant, a “non-drip” general purpose shop oil, and as a circulating oil for gears and bearings.

CLASSIFICATION:

NSF Registered H-2

TYPICAL PROPERTIES:

MYSTIK® ANTI-LEAK INDUSTRIAL OIL

Material Code	663300002
ISO Grade	100 (Recommended for 46, 68, 100)
SAE Grade	15W-40
Gravity, ASTM D 4052, °API	30.1
Density, lb/gal at 60°F	7.29
Viscosities:	
at 40°C, cSt	92.7
at 100°C, cSt	12.9
Viscosity Index	137
Flash Point, ASTM D 92, COC, °F (°C)	400 (204)
Pour Point, ASTM D 97, °F (°C)	-30 (-34)
Appearance, Color	Aqua Blue