

Mystik® Bar and Chain Lubricant

OVERVIEW




- A highly functional oil used on chain saws for suppressing dust, reducing friction and protecting the chain links, rivets, and bar from wear, heat, and corrosion.
- A great choice for loggers, as well as home and ranch users.
- Utilizes special components to reduce wear, guard against rust, and enhance metal adhesion to reduce spatter.

FEATURES & BENEFITS



- Designed for use over a wide temperature range. Clings in summer. Flows in winter.
- Lubricates and cools chain to maintain proper chain length and prolong cutter sharpness.
- Polymer additive controls spatter.
- Guards against rust.
- Protects against rivet wear.

APPLICATIONS



- For use in all brands of chain saws.

NOTE: NOT FOR USE IN ENGINES! Use Mystik JT-4® 2-Cycle Lawn and Garden Engine Oil, Material Code 663091002, where 2-cycle engine oil is specified.

PROPERTIES



Typical Properties for Mystik Bar and Chain Lubricant:

Material Code	663605002
SAE Grade	30
ISO Viscosity Grade	68
Gravity, °API ASTM D4052	28
Pounds/Gallon @ 60°F	7.4
Flash Point, COC, °F (°C) ASTM D92	295 (146)
Pour Point, °F (°C) ASTM D97	-40 (-40)
Viscosity ASTM D445	
cSt at 40°C	68
cSt at 100°C	10
Appearance, Color	Dark Amber

Mystik is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.