

**MYSTIK® LUBRICANTS  
ROCK DRILL OILS**



Date 01/10

**Heavy Duty Pneumatic Tools Oils**

**DESCRIPTION:**

Mystik Lubricants Rock Drill Oils are formulated with EP/antiwear, rust and oxidation inhibitors, a tackifier, and an emulsifier. They provide excellent extreme pressure (EP) and anti-wear performance in heavy duty pneumatic tools. May also be used as high-quality industrial slideway lubricants (way oils) or non-drip oils.

**FEATURES:**

- EP/antiwear, rust, and oxidation inhibited
- Emulsifier gives emulsification properties for extra lubricity in moist or wet conditions
- Tackiness agent reduces “splatter” and provides non-drip qualities

**APPLICATIONS:**

- Excellent recommendation for rock drills, jack-hammers, and other pneumatic tools
- Also used as EP gear lubes (API GL-3), way lubricants, and non-drip oils

**TYPICAL PROPERTIES:**

**MYSTIK® LUBRICANTS ROCK DRILL OILS**

Material Code	663813002	663814002
ISO Viscosity Grade	100	150
SAE Viscosity Grade (Approx.)	30	40
Gravity, ASTM D 287, °API	28.4	29.1
Density, lb/gal at 60°F	7.29	7.34
Flash Point, COC, ASTM D 92, °F (°C)	486 (252)	475 (246)
Pour Point, ASTM D 97, °F (°C)	-11 (-24)	5 (-15)
Viscosities:		
cSt. at 40°C	101.4	146
cSt. at 100°C	12.1	15.5
SUS at 100°F	528	764
SUS at 210°F	68	81.73
Viscosity Index	109	108
Color, ASTM D 1500	L2.5	4.0
Timken OK Load, lbs	>65	>65
Falex Load, lbs	>2000	>2000