

**M Y S T I K[®] V I S C I D L U B E[®]
O I L T R E A T M E N T**



Date 01/10

DESCRIPTION:

Mystik ViscidLube Oil Treatment is a special polymer-rich treatment. May be added to crankcase of warm, running engine, using 8-16 ozs. of Mystik ViscidLube to 4 quarts of motor oil to reduce oil consumption problems. **DO NOT OVERFILL CRANKCASE.**

Builds high temperature viscosity with small effect on low temperature fluidity. Contains an effective anti-wear and anti-oxidant additive system. Compatible with conventional and synthetic based motor oils for gasoline and diesel engines.

Mystik Viscid Lube has excellent adherence to metal. Use neat or mixed with 50% motor oil in engine repair and assembly as a pre-lubricant to protect critical parts and help with parts positioning.

FEATURES:

- Excellent pre-assembly lube
- Increases oil pressure; retards oil leakage and oil consumption
- Raises viscosity at high temperatures with minimal effect on low temperature fluidity and cold weather start-up
- Exhibits good shear stability (resistance to viscosity loss in service)
- Provides additional antiwear and antioxidation protection to prevent wear and deposits on cams, lifters, pistons, rings, and bearing

DIRECTIONS:

Add one bottle (14.0 fluid ounces) of Mystik ViscidLube Oil Treatment to four or five quarts of oil when engine is at operating temperature. For badly worn engines, use two bottles for smoother, quieter operation with less oil consumption and tail-pipe smoke.

TYPICAL PROPERTIES:

M Y S T I K[®] V I S C I D L U B E[®] O I L T R E A T M E N T

Material Code	663618002
Gravity, ASTM D 287, °API	32.0
Density, lb/gal at 60°F	7.21
Specific Gravity at 60°F	0.8655
Viscosities:	
at 40°C, cSt	9757
at 100°C, cSt	805
Viscosity Index	297
Flash Point, ASTM D 92, COC, °F (°C)	350 (177)
Pour Point, ASTM D 97, °F (°C)	0 (-18)
Color, ASTM D 1500	2.0