

**MYSTIK® LUBRICANTS
TURBINE DRIP OIL**



Date 01/10

DESCRIPTION:

Mystik Lubricants Turbine Drip Oil formulated with highly refined lubricating base oils inhibited with a foam suppressant. It is for use in dripper lubrication systems for water well line shaft bearings.

FEATURES:

- A fully refined lubricating oil inhibited with foam suppressant
- Used for lubrication by dripper systems for water well line shaft bearings

NOTE:

The EPA strongly recommends that where there is a possibility of ground water contact with the lubricant or lubricated surface, a food grade quality lubricant be used. Certain state, regional, and local Departments of Health have heeded this recommendation and now require the use of lubricants of this quality for ground water pumps.

TYPICAL PROPERTIES:

MYSTIK® LUBRICANTS TURBINE DRIP OIL

Material Code	663435002
SAE Grade	10W
ISO Grade	32
Gravity, ASTM D 287, °API	24.8
Density, lb/gal at 60°F	7.54
Specific Gravity at 60°F	0.9053
Viscosities:	
at -25°C, cP	6400
at 40°C, cSt	29.3
at 100°C, cSt	5.0
at 100°F, cSt (SUS)	150
at 210°F, cSt (SUS)	42.4
Viscosity Index	86
Flash Point, ASTM D 92, COC, °F (°C)	380 (193)
Pour Point, ASTM D 97, °F (°C)	-25 (-32)
Color, ASTM D 1500	3.0