

**M Y S T I K<sup>®</sup> J T - 4<sup>®</sup> S Y N T H E T I C 2 - C Y C L E  
S N O W M O B I L E E N G I N E O I L**



Date 01/10

**DESCRIPTION:**

Mystik JT-4 Synthetic 2-Cycle Snowmobile Engine Oil utilizes premium synthetic base oils combined with a special synthetic additive system to provide superior cold temperature protection and quick starts in extreme cold. Its unique tri-blend of synthetic components provides ideal low temperature performance and quick starts in extreme cold. This balance of synthetic components enhances fuel economy, improves cold temperature performance and high temperature thermal stability.

The special additive system is designed for specific use in Snowmobile engines. It provides the best protection against engine wear, rust and corrosion, and ensures engine cleanliness. The advanced formula used in Mystik JT-4 Synthetic 2-Cycle Snowmobile Engine Oil far exceeds Snowmobile engine requirements for an API TC, JASO FC and JASO FD quality oil.

**FEATURES:**

- Provides superior protection in temperature extremes
- Permits quick-fill lubrication flow during cold weather start-up to help reduce wear
- Promotes longer engine life through increased wear, rust and corrosion protection
- Improves equipment productivity and reliability

**RECOMMENDED:**

For use in all air-cooled or liquid-cooled 2-cycle (Injector or Premix) Snowmobile engines including those manufactured by Arctic Cat, Ski Doo, Polaris, Yamaha, and other original equipment manufacturers. Mystik JT-4 Synthetic 2-Cycle Snowmobile Engine Oil is ideal for engines operating in extreme cold temperatures and where performance demands the most from your oil.

**APPLICATIONS:**

Mystik JT-4 Synthetic 2-Cycle Snowmobile Engine Oil is recommended for use in 2-cycle Snowmobile engine applications requiring API TC, JASO FC and JASO FD quality oil.

**DO NOT USE IN OUTBOARD MARINE ENGINES!**

**TYPICAL PROPERTIES:**

**MYSTIK<sup>®</sup> JT-4<sup>®</sup> SYNTHETIC 2-CYCLE SNOWMOBILE ENGINE OIL**

Material Code	663077002
Gravity, ASTM D 287, °API	32.9
Density lbs/gal	7.17
Flash Point, PMCC, ASTM D 93, °F (°C)	194 (90)
Flash Point, ASTM D 92, COC, °F (°C)	230 (110)
Pour Point, ASTM D 97, °F (°C)	-54 (-48)
Viscosity, ASTM D 445	
cSt @ 40°C	54
cSt @ 100°C	9.2
Viscosity Index, ASTM D 2270	152
Visual Color	Purple
Sulfated Ash, ASTM D 874, m%	0.015
TBN, ASTM D 2896, mg KOH/g	4.3