

**M Y S T I K[®] J T - 4[®] S Y N T H E T I C 2 - C Y C L E
P E R S O N A L W A T E R C R A F T
E N G I N E O I L**



Date 01/10

DESCRIPTION:

Mystik JT-4 Synthetic 2-Cycle Personal Watercraft Engine Oil utilizes premium synthetic base oils combined with a special synthetic additive system to provide superior high temperature oxidation stability and wear protection. Its unique tri-blend of synthetic components provides ideal high temperature performance and quick starts in all temperatures. This balance of synthetic components enhances fuel economy, and improves high temperature thermal and oxidation stability.

The special additive system designed for specific use in Personal Watercraft engines provides the best protection against engine wear, rust and corrosion, and ensures engine cleanliness. The advanced formula used in Mystik JT-4 Synthetic 2-Cycle Personal Watercraft Engine Oil far exceeds Personal Watercraft engine requirements for an API TC, JASO FC and JASO FD quality oil.

FEATURES:

- Provides superior protection in high temperatures
- Permits quick-fill lubrication flow during start-up to help reduce wear
- Promotes longer engine life through increased wear, rust and corrosion protection
- Improves equipment productivity and reliability

RECOMMENDED:

For use in all air-cooled or liquid-cooled 2-cycle (Injector or Premix) Personal Watercraft engines including those manufactured by Sea Doo, Kawasaki, Polaris, Yamaha, and other original equipment manufacturers. Mystik JT-4 Synthetic 2-Cycle Personal Watercraft Engine Oil is ideal for engines operating in high temperatures and where performance demands the most from your oil.

APPLICATIONS:

Mystik JT-4 Synthetic 2-Cycle Personal Watercraft Engine Oil is recommended for use in 2-cycle Personal Watercraft engine applications requiring API TC, JASO FC, and JASO FD quality oil.

DO NOT USE IN OUTBOARD MARINE ENGINES!

TYPICAL PROPERTIES:

MYSTIK[®] JT-4[®] SYNTHETIC 2-CYCLE PERSONAL WATERCRAFT ENGINE OIL

Material Code	663076002
Gravity, ASTM D 287, °API	32.9
Density lbs/gal	7.17
Flash Point, PMCC, ASTM D 93, °F (°C)	194 (90)
Flash Point, ASTM D 92, COC, °F (°C)	230 (110)
Pour Point, ASTM D 97, °F (°C)	-54 (-48)
Viscosity, ASTM D 445	
cSt @ 40°C	54
cSt @ 100°C	9.2
Viscosity Index, ASTM D 2270	152
Visual Color	Purple
Sulfated Ash, ASTM D 874, m%	0.015
TBN, ASTM D 2896, mg KOH/g	4.3