

**M Y S T I K<sup>®</sup> J T - 4<sup>®</sup> S Y N T H E T I C 4 - C Y C L E  
A L L - T E R R A I N V E H I C L E M O T O R O I L  
S A E 0 W - 4 0 A N D S A E 1 0 W - 4 0**



Date 07/15

**DESCRIPTION:**

Mystik JT-4 Synthetic 4-Cycle All-Terrain Vehicle Motor Oil SAE 0W-40 and SAE 10W-40 utilize premium synthetic base oils combined with a special synthetic additive system to provide outstanding protection for high performance All-Terrain Vehicle (ATV) and Utility Vehicle (UTV) engines. The synthetic components provide optimum high and low temperature performance while minimizing volatility. This balance of synthetic components enhances fuel economy, improves cold temperature performance, and high temperature thermal and oxidation stability.

The special additive system is designed for specific use in ATV and UTV engines. It provides the best protection against engine wear, rust and corrosion, and ensures engine cleanliness. The advanced formula used in Mystik JT-4 Synthetic 4-Cycle All-Terrain Vehicle Motor Oil, available in SAE 0W-40 and SAE 10W-40 grades, meets gasoline powered ATV and UTV engine requirements for an API SL, JASO MA and NMMA FC-W quality oil.

**FEATURES:**

- Provides superior protection in extreme hot and cold temperatures
- Permits quick-fill lubrication flow during cold weather start-up
- Promotes longer engine life through increased wear, rust and corrosion protection
- Provides excellent thermal and oxidation stability
- Improves equipment productivity and reliability

**RECOMMENDED:**

For use in 4-cycle gasoline powered ATV and UTV including those manufactured by Arctic Cat, Bombardier, Honda, Kawasaki, Polaris, Yamaha, and other original equipment manufacturers. Ideal for high performance engines operating in extreme low and high temperatures and where performance demands the most from your oil. Select the SAE 0W-40 grade, if frequent usage at low temperatures is expected. Consult owner's manual for proper lubricant selection.

**APPLICATIONS:**

Mystik JT-4 Synthetic All-Terrain Vehicle Motor Oil is recommended for use in 4-cycle gasoline powered ATV and UTV engine applications requiring an API SL, JASO MA and NMMA FC-W quality oil. It is designed to be used in wet clutch applications that require JASO MA quality oil.

**TYPICAL PROPERTIES:**

**M Y S T I K<sup>®</sup> J T - 4<sup>®</sup> S Y N T H E T I C 4 - C Y C L E A L L - T E R R A I N V E H I C L E M O T O R O I L**

<b>Material Codes</b>	<b>663079002</b>	<b>663080002</b>
SAE Grade	SAE 0W-40	SAE 10W-40
Gravity, ASTM D 287, °API	33.8	31.9
Density, lbs/gal	7.13	7.21
Flash Point, ASTM D 92, COC, °F (°C)	428 (220)	453 (234)
Pour Point, ASTM D 97, °F (°C)	-56 (-51)	-22 (-30)
Viscosity, ASTM D 445		
cSt @ 40°C	93	98.4
cSt @ 100°C	14.8	14.9
Viscosity Index, ASTM D 2270	166	158
CCS Viscosity, cP (°C), ASTM D 5293	6000 (-35)	5660 (-25)
NOACK Volatility, ASTM D 5800, % Loss	7	9
Color, ASTM D 1500	2.5	2.5
Sulfated Ash, ASTM D 874, m%	0.9	1.0
TBN, ASTM D 2896, mg KOH/g	9.5	9.2

Mystik and JT-4 are registered trademarks protected by federal law. All other registered trademarks or trademarks are the property of their respective owners.