

MYSTIK® JT-4® SYNTHETIC 4-CYCLE ALL-TERRAIN VEHICLE MOTOR OILS



Date 06/18

DESCRIPTION:

Mystik JT-4 Synthetic 4-Cycle All-Terrain Vehicle Motor Oils utilize premium synthetic base oils combined with a special additive system to provide outstanding protection for high performance All-Terrain Vehicle (ATV) and Utility Vehicle (UTV) engines. These full synthetic formulas provide optimum high and low temperature performance while minimizing volatility. This balance of synthetic technologies enhance fuel economy, improve cold temperature performance, and high temperature thermal and oxidation stability.

The advanced additive systems are specifically designed for use in ATV and UTV engines. They provide superior protection against engine wear, rust and corrosion, and ensures engine cleanliness. Mystik JT-4 Synthetic 4-Cycle All-Terrain Vehicle Motor Oils, available in SAE 0W-40, SAE 10W-40 and SAE 10W-50 grades, provide extra protection for gasoline powered ATV and UTV engines requiring a JASO MA quality oil.

FEATURES:

- Protect in extreme hot and cold temperatures
- Permit lubrication flow during cold weather start-up
- Promote longer engine life by reducing wear, rust and corrosion
- Provide excellent thermal and oxidation stability
- Improve equipment productivity and reliability

RECOMMENDED:

For use in 4-cycle gasoline powered ATV and UTV engines including those manufactured by Arctic Cat, Bombardier, Honda, Kawasaki, Polaris (including 1000 ProStar), Yamaha, and other original equipment manufacturers. Ideal for high performance engines operating in extreme low and high temperatures and where performance demands the most from your oil. Select the SAE 0W-40 grade, if frequent usage at low temperatures is expected. Consult your owner's manual for proper lubricant selection.

APPLICATIONS:

Mystik JT-4 Synthetic All-Terrain Vehicle Motor Oils are recommended for use in 4-cycle gasoline powered ATV and UTV engine applications requiring a JASO MA quality oil. Designed to be used in wet clutch applications that require JASO MA quality oil.

TYPICAL PROPERTIES:

MYSTIK® JT-4® SYNTHETIC 4-CYCLE ALL-TERRAIN VEHICLE MOTOR OILS

Material Codes	663079002	663080002	663085002
SAE Grade	0W-40	10W-40	10W-50
Gravity, ASTM D287, °API	33.8	31.9	33.5
Density, lbs/gal	7.13	7.21	7.14
Flash Point, ASTM D92, COC, °F (°C)	428 (220)	453 (234)	457 (236)
Pour Point, ASTM D97, °F (°C)	-56 (-51)	-22 (-30)	-39 (-39)
Viscosity, ASTM D445			
cSt @ 40°C	93	98.4	126.6
cSt @ 100°C	14.8	14.9	17.85
Viscosity Index, ASTM D2270	166	158	157
CCS Viscosity, cP (°C), ASTM D5293	6000 (-35)	5660 (-25)	6592 (-25)
NOACK Volatility, ASTM D5800, % Loss	7.0	9.0	7.4
Color, ASTM D1500	2.5	2.5	2.5
Sulfated Ash, ASTM D874, m%	0.9	1.0	1.0
TBN, ASTM D2896, mg KOH/g	9.5	9.2	8.05

Mystik and JT-4 are registered trademarks protected by federal law. All other registered trademarks or trademarks are the property of their respective owners.

Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.