


Mystik[®] Synthetic Multi-Vehicle ATF

OVERVIEW




- Contains the highest-quality synthetic base stock combined with a state-of-the-art additive system to provide superior performance in automatic and powershift transmissions.
- Suitable for use in transmissions calling for Ford MERCON[®] V, Ford MERCON (obsolete), General Motors DEXRON[®]-IIIH (obsolete), and Allison C-4 type fluids.

FEATURES & BENEFITS




- Superior oxidation and thermal stability.
- Outstanding antiwear performance for protection of transmission hardware.
- Excellent cold-temperature flow properties.
- Compatible with a wide range of seal materials to prevent transmission leaks.
- Can be used in most vehicles.
- Multi-vehicle compatibility enables inventory optimization without the use of ATF supplements.

APPLICATIONS



Suitable for use in GM, Ford, Toyota, Honda, Nissan, Hyundai, and other imported vehicles where the following specifications are called for:

- Ford MERCON and MERCON V* (Not recommended for use in California)
- GM DEXRON-II and DEXRON-III
- Allison C-4, TES-295 (not OEM-approved), TES-389 (not OEM-approved)
- BMW LT-71141, ETL-7045E, 2634, 8072B.
- Nissan/Infiniti Nissan ATF, Matic D, Matic J, and Matic K
- Mitsubishi Diamond SP-II and SP-III
- Hyundai/KIA SP-II and SP-III
- Toyota/Lexus Type T, T-III and T-IV
- Honda/Acura ATF-Z1 (except in CVTs)
- Mercedes Benz 236.3; .5; .6; .7; .9; .10; and .11; ATF 3403 M-115
- Volvo Standard 1273,41 (Transmission oil 97341); 1161521; 1161540 / 1161640 – JWS 3309

APPLICATIONS

- Volkswagen/Audi G052025 (A2); G052055; G052162 (A1, A2); G052990 (A2); G055025 (A2); GUS000162
- ZF TE-ML 11A; 11B
- JASO 1A
- MAN 339A
- Mazda Type T-IV
- Subaru ATF-HP
- Renault Matic D2

*Please note that California law prohibits manufacturers of multi-vehicle ATF from recommending products in certain applications where the viscometrics do not match those of official OEM specifications. CITGO therefore does not recommend the use of Mystik® Synthetic Multi-Vehicle ATF in these applications in California.

Do not use Mystik Synthetic Multi-Vehicle ATF in vehicles calling for Type F, DEXRON VI, MERCON SP, MERCON LV, Toyota/Lexus WS, and CVTs.

Refer to equipment owner's manual for proper lubricant recommendation.

PROPERTIES**Typical Properties for Mystik Synthetic Multi-Vehicle ATF:**

Material Code	633136002
Viscosity	
cSt at 40°C	35
cSt at 100°C	7.2
Viscosity Index	178
Specific Gravity @ 60 °F	0.851
Pour Point ASTM D97, °F (°C)	-60 (-51)
Brookfield Viscosity @ -40 °C, cP	9600
Appearance	Red

©2019 CITGO Petroleum Corporation

The Mystik Lubricants name, logo and all related marks are registered trademarks protected by federal law. All other registered trademarks or trademarks are the property of their respective owners.