

**MYSTIK® JT-4® SYNTHETIC 4-CYCLE
PERSONAL WATERCRAFT MOTOR OIL
SAE 10W-40**



Date 01/10

DESCRIPTION:

Mystik JT-4 Synthetic 4-Cycle Personal Watercraft Motor Oil SAE 10W-40 utilizes premium synthetic base oils combined with a special synthetic additive system to provide superior high oxidation stability and wear protection. Its unique tri-blend of synthetic components enhances fuel economy and improves high temperature thermal stability. The special additive system is designed for specific use in Personal Watercraft engines. It provides the best protection against engine wear, rust and corrosion, and ensures engine cleanliness. The advanced formula used in Mystik JT-4 Synthetic 4-Cycle Personal Watercraft Motor Oil SAE 10W-40 far exceeds Personal Watercraft engine requirements for an API SL, JASO MA and NMMA FC-W quality oil.

FEATURES:

- Provides superior protection in harsh marine environments
- Permits rapid start-ups
- Promotes longer engine life through increased wear, rust and corrosion protection
- Improves equipment productivity and reliability

RECOMMENDED:

For use in 4-cycle Personal Watercrafts including those manufactures by Sea Doo, Kawasaki, Polaris, Yamaha, and other original equipment manufacturers. Mystik JT-4 Synthetic 4-Cycle Personal Watercraft Motor Oil SAE 10W-40 is ideal for engines operating in harsh marine environments and where performance demands the most from your oil.

APPLICATIONS:

Mystik JT-4 Synthetic 4-Cycle Personal Watercraft Motor Oil SAE 10W-40 is recommended for use in Personal Watercraft engine applications requiring an API SL, JASO MA and NMMA FC-W quality oil. It can also be used in four-cycle outboard marine engines specifying NMMA FC-W motor oil.

DO NOT USE IN 2-CYCLE ENGINES!

TYPICAL PROPERTIES:

**MYSTIK® JT-4® SYNTHETIC 4-CYCLE PERSONAL WATERCRAFT ENGINE OIL
SAE 10W-40**

Material Code	663082002
Gravity, ASTM D 287, °API	31.9
Density lbs/gal	7.21
Flash Point, ASTM D 92, COC, °F (°C)	453 (234)
Pour Point, ASTM D 97, °F (°C)	-22 (-30)
Viscosity, ASTM D 445	
cSt @ 40°C	98.4
cSt @ 100°C	14.9
Viscosity Index, ASTM D 2270	158
CCS Viscosity, cP (°C), ASTM D 5293	5660 (-25)
NOACK Volatility, ASTM D 5800, % Loss	9
Color, ASTM D 1500	2.5
Sulfated Ash, ASTM D 874, m%	1.0
TBN, ASTM D 2896, mg KOH/g	9.2