

MYSTIK® JT-4® PREMIUM  
HIGH PERFORMANCE LOWER UNIT  
GEAR LUBRICANT



Date 01/10

**DESCRIPTION:**

Mystik JT-4 Premium High Performance Lower Unit Gear Lubricant is formulated specifically for the marine industry. It contains the latest generation of a proprietary EP additive system, designed to provide maximum protection against wear, rust, corrosion and deposits.

**QUALITIES:**

This improved gear lubricant, specifically designed for boating applications, offers top level protection, surpassing other marine gear lubricants using GL-4 and GL-5 80W-90 technology:

- Superior EP lubrication and corrosion protection in the presence of moisture (fresh and sea water).
- Improved gear protection for shock load conditions encountered with harsh startup engagement, power reversal, and propeller entanglement.

**APPLICATIONS:**

Recommended for use in all outboard and stern drive gear units specifying SAE 90, 80W-90 or 85W-90, including OMC Type "C." Includes MerCruiser, OMC Cobra, Volvo stern drives and Mercury, Evinrude, Johnson, Mariner, Yamaha, Suzuki, and Force outboards.

**TYPICAL PROPERTIES:**

**MYSTIK® JT-4® PREMIUM HIGH PERFORMANCE LOWER UNIT GEAR LUBRICANT**

SAE GRADE	85W-90
Material Code	663090002
Gravity, ASTM D 4052, °API	26.3
Density, lb/gal at 60°F	7.5
Flash Point, ASTM D 92, COC, °F (°C)	420 (216)
Viscosity, cSt at 100°C	16.0
Brookfield Viscosity, -23°C, cP	102,000
Pour Point, ASTM D 97, °F (°C)	-15 (-26)
Channel Point, °F (°C), Max	-31 (-35)
Color, Visual	Blue
Foam Test, ASTM D 892	Pass
Copper Corrosion, 3 hrs at 250°F	Pass