


Mystik[®] JT-6[®] High Performance Marine Grease

OVERVIEW




- A smooth, tacky blue grease with outstanding water resistance, designed to provide excellent lubrication for greased chassis points and other wet-environment applications.
- Combines an anhydrous calcium thickener system, a special polymer, and a proprietary additive system to ensure superior performance against rusting in both fresh and sea water marine applications.

FEATURES & BENEFITS



- Premium high-performance extreme pressure (EP) marine grease.
- Outstanding water washout resistance and protection against saltwater corrosion.
- Excellent wear protection and load-carrying capability.
- Polymer-fortified for excellent metal adhesion.
- Lubricates well over a wide temperature range (0 to 250°F).

APPLICATIONS



- Recommended for marine applications including greased automotive chassis points, trailer wheel bearings, bearing buddies, boat lifts, hydraulic jack plates, steering components, tilt and trim systems, and more.
- Excellent for non-marine applications where a general multi-purpose EP grease with outstanding water and corrosion resistance is desired: water pumps, fifth wheels, and other equipment operating in wet conditions.
- Not recommended for disc brake wheel bearings.
- Refer to equipment owner's manual for proper lubricant recommendation.

PROPERTIES**Typical Properties for Mystik JT-6 High Performance Marine Grease:**

Material Code	665065002
NLGI Consistency Grade	2
Thickener Type	Anhydrous Calcium
Texture	Smooth, Adhesive
Color, Observed	Blue
Worked Penetration, ASTM D217	265-295
Approximate Temperature Range, °F (°C)	0 to 250 (-18 to 121)
Dropping Point, ASTM D566, °F (°C)	290 (143)
Water Washout, ASTM D1264, % loss @ 100°F	0.9
Oil Separation, ASTM D1742, % loss	<1
Rust Prevention, ASTM D1743, rating	Pass
Copper Corrosion, ASTM D4048, rating	1b
Synthetic Sea Water Corrosion, ASTM D5969, rating	Pass
Timken OK Load, ASTM D2509, lb	55
Four-Ball Weld, ASTM D2596, kgf	250
Four-Ball Wear, ASTM D2266, mm	0.6
Base Oil Viscosity: 40°C, cSt	1080

Mystik and JT-6 are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.

Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.