

**MYSTIK® LUBRICANTS
FARM OILS**



Date 01/10

General Purpose, “Non-Detergent Type” Oils

DESCRIPTION:

Mystik Lubricants Farm Oils are lubricants for general purpose farm or shop use. They are fully refined lubricants with additive to ensure some oxidation, corrosion and foam inhibition and may contain additional additives used in lubricant manufacture. Farm Oils come in SAE 10W, 20W-20 and 30 viscosity grades and meet the obsolete API SB and SA classifications. Non-detergent oils of this type are not recommended for modern gasoline or diesel engines. They may be used as general machine oil or for non-critical, hydraulic or compressor service.

TYPICAL PROPERTIES:

MYSTIK® LUBRICANTS FARM OILS

Material Code	663100002	663101002	663102002
SAE Grade	10W	20W-20	30
ISO Grade (Approx.)	32	68	100
Density, lb/gal at 60°F (Approx.)	7.25	7.3	7.4
Viscosities (Approx.):			
at -20°C, cP	<3500	<7000	—
at 100°C, cSt	5.4	8.4	11
at 40°C, cSt	32	66	100
at 210°F, SUS	44	54	64
at 100°F, SUS	165	340	525
Viscosity Index	99	95	94
Flash Point, ASTM D92, °F (°C)	390 (199)	400 (204)	425 (218)
Pour Point, ASTM D97, °F (°C)	-30 (-34)	-15 (-23)	-5 (-20)
Color, ASTM D 1500	2.0	3.0	3.5

FEATURES:

- (1) Fully refined virgin oils
- (2) Low carbon content
- (3) Treated with antifoam and antioxidant additives

NOTE: Consult machinery operator's manual for proper viscosity grade. For gasoline or diesel engines, consider Mystik J-8 engine oils.