

MYSTIK® LUBRICANTS

C - 3 F L U I D



Date 01/10

DESCRIPTION:

Mystik Lubricants C-3 Fluid is a SAE 10W-20 viscosity grade with detergent/dispersant, antiwear, antirust, antioxidant, and antifoam compounding.

QUALITIES:

Mystik Lubricants C-3 Fluid meets the performance requirements for Allison Type C-3 fluid. It also supersedes and may be used where former Types C-1 and C-2 were specified.

APPLICATION:

Mystik Lubricants C-3 Fluid was designed specifically for use in older Allison power shift transmissions and torque converters. It can also be used in many other applications where Allison Type C-3 fluids are recommended.

TYPICAL PROPERTIES:

MYSTIK® LUBRICANTS C-3 FLUID

Material Code	663530002
SAE Grade	10W-20
Gravity, ASTM D 4052, °API	28.7
Density, lb/gal	7.355
Specific Gravity	0.8833
Viscosities:	
at -18°C, cP	1725
at 40°C, cSt	35.4
at 100°C, cSt	5.7
Viscosity Index	99
Flash Point, ASTM D 82, °F (°C)	405 (207)
Pour Point, ASTM D 97, °F (°C)	-25 (-32)
Color, ASTM D 1500	2.0