MYSTIK® JT-8® SYNTHETIC BLEND SUPER HEAVY DUTY ENGINE OILS SAE 10W-40 AND SAE 15W-50

Date 05/18

DESCRIPTION:

Mystik JT-8 Synthetic Blend Super Heavy Duty Engine Oil SAE 10W-40 provides an improvement in cold weather start up lubrication while providing excellent wear protection at higher operating temperatures.

Mystik JT-8 Synthetic Blend Super Heavy Duty Engine Oil SAE 15W-50 is designed for the equipment owner operating with older equipment with higher hours or miles that can benefit from a higher viscosity grade heavy duty engine oil.

Both SAE grades are engineered to provide excellent protection for equipment operating in severe conditions and will provide extended diesel engine life.

Mystik JT-8 Synthetic Blend Super Heavy Duty Engine Oils SAE 10W-40 and SAE 15W-50 are recommended for commercial over-the-road fleets, construction equipment, buses and other similar diesel-powered applications where premium quality engine is required.

TYPICAL PROPERTIES:

MYSTIK® JT-8® SYNTHETIC BLEND SUPER HEAVY DUTY ENGINE OILS SAE 10W-40 AND SAE 15W-50

Material Code	**663002**	**663004**
SAE Grade	10W-40	15W-50
API Service Category	CK-4	CI-4 Plus
Gravity, ASTM D 4052, °API	31.5	30.3
Density, lbs/gal	7.23	7.28
Flash Point, ASTM D 92 (COC), °F (°C)	442 (228)	440 (227)
Viscosity, ASTM D 445, cSt at 40°C	105	151
cSt at 100°C	15.6	19.5
Viscosity Index, ASTM D 2270	157	148
CCS Viscosity, ASTM D 5293, cP	5700 at -25C	5300 at -20C
MRV Pumpability, ASTM D 4684, cP	39,000 at -30C	23,100 at -25C
MRV Yield Stress at -25°C, ASTM D 4684	<35 at -30C	<35 at -25C
Pour Point, ASTM D 97, °F (°C)	-49 (-45)	49 (-45)
Color, ASTM D 1500	L3.5	L4.0
Sulfated Ash, ASTM D 874, m%	1.0	1.0

Mystik and JT-8 are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.