

**MYSTIK® JT-6®  
CERAMIC HI-TEMP GREASE**



Date 02/16

**DESCRIPTION:**

Mystik JT-6 Ceramic Hi-Temp Grease is a cutting edge premium Ceramic Hi-Temp grease utilizing high performance ceramic particle technology. This high temperature Lithium Complex grease combines excellent multi-purpose properties with that of ceramic technology.

**APPLICATIONS**

Mystik JT-6 Ceramic Hi-Temp Grease provides excellent service in a variety of industrial bearings, bushings, conveyors, gears, slides and wear plates. The industries served include agriculture, construction equipment, mining operations, sand/gravel plants, general manufacturing, material handling, hinge pins, conveyors, and pelleting. Consult owner’s manual for proper lubricant selection.

**TYPICAL PROPERTIES:**

**MYSTIK® JT-6® CERAMIC HI-TEMP GREASE**

<b>Material Code</b>	<b>665097002</b>
NLGI Consistency Number	2
Thickener	Lithium Complex
Texture	Smooth, Adhesive
Color	Opaque Tan
Worked 60 Penetration, ASTM D217	265-295
Dropping Point, ASTM D2265, °F (°C)	500 (260)
Rust Prevention, ASTM D1743, rating	Pass
Four-Ball EP Weld Point, ASTM D2596, kgf	315
Four-Ball Wear, ASTM D2266, mm	0.46
Four-Ball Load Wear Index, ASTM D2596	50
Approximate Temperature Range, °F (°C)	-10 to 325 (-23 to 163)

Mystik and JT-6 are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.